

# VBCBI0516 - 5 Ton Capacity



## STANDARD SPECIFICATIONS

<b>GVWR:</b>	12,290 lbs.	<b>Axles:</b>	(2) 3,500 lb AL-KO ultralube w/Brakes
<b>Empty Weight:</b>	2,290 lbs.	<b>Suspension:</b>	Double Eye Spring
<b>Maximum Payload:</b>	10,000 lbs. w/adequate hitch load	<b>Brakes:</b>	Electric w/break-a-way
<b>Overall Length:</b>	23'	<b>Wheels:</b>	15" x 6" White Spoke 6-bolt
<b>Deck Length:</b>	16'	<b>Tires:</b>	225/75 D15 (Bias)
<b>Overall Width:</b>	96"	<b>Jack Capacity:</b>	5,000 lb w/foot
<b>Deck Width:</b>	77"	<b>Main Frame:</b>	3" x 5" x 5/16" Angle @ 8.2#
<b>Deck Height:</b>	20"	<b>Crossmembers:</b>	3" Channel @ 3.5#
<b>Ramps:</b>	4' Cleated Fully Adjustable	<b>Decking:</b>	2" x 8" Treated Pine
<b>Hitch:</b>	Fixed 2 5/16" ball coupler	<b>Tie Downs:</b>	Stake Pockets
<b>Hitch Height:</b>	20"	<b>Lights:</b>	DOT Sealed Rubber-Mounted
<b>Fenders:</b>	Diamond Plate	<b>Colors:</b>	Black

## OPTIONS

VBCBI0514 - 5 Ton Capacity 14'	TC - Trickle Charger for Break-A-Way
STM - Spare Tire Mount	RU - Radial Upgrade (ST225/75R15")
MW - Modular Wiring	CO- Color Options: Yellow, Red, Blue or Green
LTBL - Lockable Toolbox Lid	6W102 - 6' Wide to 102" Wide

## MISCELLANEOUS

\* Red = Differences between this model & the Pro Series HBC10 5 Ton.

Hudson Bros Trailer Mfg. Inc - 1508 Hwy 218 West - Indian Trail, NC 28079 - Ph: 704.753.4723  
[www.hudsontrailers.com](http://www.hudsontrailers.com)