


VTMBH0621 - 6 Ton Capacity



STANDARD SPECIFICATIONS

GVWR:	15,920 lbs.	Axles:	(2) 6K AL-KO ultralube w/Brakes
Empty Weight:	3,920 lbs.	Suspension:	Multi-Leaf Spring
Maximum Payload:	12,000 lbs. w/adequate hitch load	Brakes:	Electric 12" x 2" w/ break-a-way
Overall Length:	28' 6"	Wheels:	16" x 6" Single 8-Bolt
Deck Length:	21' (18' Flat w/ 3' Beavertail)	Tires:	7.50-16LT (Bias)
Overall Width:	96"	Jack Capacity:	7,000 lb. drop foot
Deck Width:	96"	Main Frame:	8" Channel @ 11.5#
Deck Height:	35"	Crossmembers:	4" Channel @ 4.5#
Beavertail:	3' Wood	Side Rail:	6" Channel @ 8.2#
Ramps:	5' Cleated	Decking:	2" x 8" Treated Pine
Hitch:	Adj. 2 1/2" Eye	Tie Downs:	Rub Rail w/ Stake Pockets
Hitch Height:	21"-25"	Lights:	DOT Sealed Rubber-Mounted
Tongue:	Cold Form	Colors:	Black

OPTIONS

VTMBH0619 - 6 Ton Capacity 19' (16' flat w/ 3' beavertail)	8WARL - Additional Ramp Length (1' Maximum)
VTMBH0623 - 6 Ton Capacity 23' (20' flat w/ 3' beavertail)	RU - Radial Upgrade (ST235/85R16")
LTB - Lockable Toolbox	MW - Modular Wiring
STM - Spare Tire Mount	CO - Color Options: Yellow, Red, Blue or Green
2 5/16" HDB - 2 5/16" Heavy Duty Ball Hitch	8W102 - 8' Wide to 102" Wide

MISCELLANEOUS

* Red = Differences between this model & the Pro Series HTM 6 Ton.

Hudson Bros Trailer Mfg. Inc - 1508 Hwy 218 West - Indian Trail, NC 28079 - Ph: 704.753.4723
www.hudsontrailers.com