

VTMGG0723 - 7 Ton Capacity



STANDARD SPECIFICATIONS

GVWR:	18,630 lbs.	Axles:	(2) 7K AL-KO ultralube w/Brakes
Empty Weight:	4,630 lbs.	Suspension:	Multi-Leaf Spring
Maximum Payload:	14,000 lbs. w/adequate hitch load	Brakes:	Electric 12" x 2" w/ break-a-way
Overall Length:	33'	Wheels:	16" x 6" Single 8-Bolt
Deck Length:	23' (20' flat w/ 3' beavertail)	Tires:	LT235/80R16" 10-PR
Overall Width:	96"	Jack Capacity:	12,000 lb w/ drop foot
Deck Width:	96"	Main Frame:	8" Channel @ 11.5#
Deck Height:	35"	Crossmembers:	4" Channel @ 4.5#
Beavertail:	3' w/wood	Side Rail:	6" Channel @ 8.2#
Ramps:	5' Cleated	Decking:	2" x 8" Treated Pine
Hitch:	Adj. 2 5/16" ball	Tie Downs:	Rub Rail w/ Stake Pockets
Hitch Height:	42" Adjustable	Lights:	DOT Sealed Rubber-Mounted
Tongue:	Gooseneck w/ Tool Tray	Colors:	Black

OPTIONS

VTMGG0725 - 7 Ton Capacity 25' (22' flat w/ 3' beavertail)	DSSLG - Dual Single Speed Landing Gear
STM - Spare Tire Mount	MW - Modular Wiring
LTBL - Lockable Toolbox Lid	CO- Color Options: Yellow, Red, Blue or Green
KP - Adj. King Pin	8W102 - 8' Wide to 102" Wide

MISCELLANEOUS

* Red = Differences between this model & the Pro Series HTMG 7 Ton.

Hudson Bros Trailer Mfg. Inc - 1508 Hwy 218 West - Indian Trail, NC 28079 - Ph: 704.753.4723
www.hudsontrailers.com