

HBC 10 14' - 4 Ton



Standard Features

2" x 8" Treated Pine Deck	Diamond Plate Fenders
(2) 4500 lb. Dexter Axles	7:00 x 14.5" 8-ply Tires
Adjustable 2 5/16" Ball Hitch	Electric Brakes w/Break-A-Way

Standard Specifications

GVWR	10,230 lbs.	Suspension	Multi-Leaf Spring
Empty Weight	2,230 lbs.	Brakes	Electric / 12" x 2"
Maximum Payload	8,000 lbs. W/adequate hitch load	Wheels	14.5" x 6" Donut Type
Overall Length	20'	Tires	7:00 x 14.5 8-ply
Deck Length	14'	Jack Capacity	2,000 lb. Flip-up
Ramps	4' Cleated Fully Adjustable	Main Frame	3" x 5" x 5/16" Angle @ 8.2#
Overall Width	96"	Crossmembers	3" Channel@ 3.5#
Deck Width	77"	Decking	2" x 8" Treated Pine
Deck Height	20"	Tie Downs	4" Stake Pockets
Hitch	2 5/16" Ball Coupler	Lights	DOT Sealed Rubber-Mounted
Hitch Height	15" to 23"	Colors	Yellow or Black
Axles	2-4500 lb. Dexter		

Options

6WGN - Gooseneck w/Adjustable 2 5/16" Ball Hitch	WIR - Wood Insert Ramps
TBB - Toolbox Bottom in Tongue	6WSATG - 6' Wide Spring Assisted Tailgate
LTBL - Lockable Toolbox Lid	6WSSATG - 6' Wide Split Spring Assisted Tailgate
6WOD - 2" x 8" Treated Oak Deck	MW - Modular Wiring
2 1/2" IH - 2 1/2" Adjustable Eye Hitch	TC - Trickle Charger for Break-A-Way
6W102 - 102" Wide w/82" Deck Width	STM - Spare Tire Mount
6WADE - Extra Deck Length (2' Maximum)	4 1/2T - 4 1/2 Ton w/8:00 x 14.5 12-ply Tires
JUZKTO7K - 7000 lbs. Jack	CO - Color Options: Red, Blue or Green