

HSE18 - 8' Wide - 6 Ton



Standard Features

2" x 8" Treated Pine Deck	12,000 lb. Heavy Duty Landing Gear
(2) 6K Dexter Axles w/E-Z Lube Bearings	16" 10-ply Radial Tires
Tool Tray in Tongue	Electric Brakes w/Break-A-Way

Standard Specifications

GVWR	14,950 lbs.	Suspension	Multi-Leaf Spring
Empty Weight	2,950 lbs.	Brakes	Electric / 12" x 2"
Maximum Payload	12,000 lbs. w/adequate hitch load	Wheels	16" x 6" Single B-bolt
Overall Length	25'	Tires	LT235/85R16" 10-ply
Deck Length	19' (16' flat)	Jack Capacity	12,000 lbs.
Beavertail	3' w/wood	Main Frame	8" Channel @ 11.5#
Ramps	5' cleated w/spring assist	Crossmembers	4" Channel @ 4.5#
Overall Width	96"	Side Rails	6" Channel @ 8.2#
Deck Width	96"	Decking	2" X 8" Treated Pine
Deck Height	31"	Tie Downs	Rub Rail w/Stake Pockets
Hitch	2 1/2" Eye	Lights	DOT Sealed Rubber Mounted
Hitch Height	17" to 21"	Colors	Yellow or Black
Axles	2-6K Dexter		

Options

8WGN - Gooseneck w/Adjustable 2 5/16" Ball Hitch	8WADL - Additional Deck Length (4' Maximum)
LTBL - Lockable Toolbox Lid	8W102 - 102" Wide
8WOD - 2" x 8" Treated Oak Deck	TC - Trickle Charger for Break-A-Way
7KA - 7K Dexter Axles w/16" 14-ply tires	STM - Spare Tire Mount
MW - Modular Wiring	8WSATG - 8' Wide Spring Assisted Tailgate
8WARL - Additional Ramp Length (1' Maximum)	8WSSATG - 8' Wide Split Spring Assisted Tailgate
WIR - Wood Insert Ramps	3"TH - 3" Eye Hitch
2 5/16"HDB - 2 5/16" Heavy Duty Ball Hitch	CO - Color Options: Red, Blue or Green