

HSLT18 - 6 Ton Tilt



Standard Features

2" x 8" Treated Pine Deck	Diamond Plate Fenders
(2) 6K Dexter Axles w/E-Z Lube Bearings	LT235 85/R 16" 10-ply Radial tires
Adjustable 2 1/2" Eye Hitch	Electric Brakes w/Break-A-Way

Standard Specifications

GVWR	15,310 lbs.	Suspension	Multi-Leaf Spring
Empty Weight	3,310 lbs.	Brakes	Electric / 12" x 2"
Maximum Payload	12,000 lbs. w/adequate hitch load	Wheels	16" x 6" Single 8-bolt
Overall Length	24'	Tires	LT235/85R16" 10-ply
Deck Length	15' flat w/3' taper	Jack Capacity	7,000 lbs.
Approach Plate	Full Width	Main Frame	6" x 4" x 3/8" Angle @ 12.3#
Overall Width	102"	Crossmembers	3" Channel @ 3.5#
Deck Width	82"	Decking	2" X 8" Treated Pine
Deck Height	22"	Tie Downs	Rub Rail w/Stake Pockets
Hitch	2 1/2" Eye	Lights	DOT Sealed Rubber-Mounted
Hitch Height	16" to 20"	Colors	Yellow or Black
Axles	2-6K Dexter		

Options

6WGN - Gooseneck w/Adjustable 2 5/16" Ball Hitch	6WADL - Extra Deck Length (2' Maximum)
LTBL - Lockable Toolbox Lid	STM - Spare Tire Mount
6WOD - 2" x 8" Treated Oak Deck	TC - Trickle Charger for Break-A-Way
MW - Modular Wiring	2 5/16"HDB - 2 5/16" Heavy Duty Ball Hitch
JU7KT012K - 12,000 lb. Heavy Duty Landing Gear	CO - Color Options: Red, Blue or Green
3"EH - 3" Eye Hitch	