

HSC - 3 1/2 Ton Capacity



Standard Specifications

GVWR	9,190 lbs.	Axles	(2) 3,500 lb. E-Z Lube Dexter w/Brakes
Empty Weight	2,190 lbs.	Suspension	Double Eye
Maximum Payload	7,000 lbs. w/Adequate hitch load	Brakes	Electric
Overall Length	22' 5"	Wheels	14" x 5" White Spoke 5-bolt
Deck Length	18' (13' Flat w/5' Tapered Beavertail)	Tires	ST215/75R14" 6 PR
Overall Width	102"	Jack Capacity	5,000 lb w/Foot
Deck Width	84 1/2"	Main Frame	4" Channel
Deck Height	21"	Tongue	4" Channel Wrap Around
Beavertail	5' Gradual Slope for Easy Loading	Decking	Full Diamond Plate w/Movable Wheel Stops
Ramps	5' Slide Out w/Diamond Plate	Tie Downs	D-Rings
Hitch	2 5/16" Ball Coupler	Lights	DOT Approved
Hitch Height	17"	Colors	Black

Options

STM - Spare Tire Mount	TC - Trickle Charger for Break-A-Way
RF - Removable Fender	STR - Spare Tire & Rim
ADR - Additional D-Rings	CO - Color Options: Red, Blue or Green