

HDDFZ - 25 Ton Capacity



Standard Specifications

GVWR	64,000 lbs.	Axles	(2) 20K Airbrake Oil Bath Dexter
Empty Weight	14,000 lbs.	Suspension	Hutch 9700
Maximum Payload	50,000 lbs. w/Adequate hitch load	Brakes	Air w/ABS & ASA 12 1/4" x 7 1/2"
Overall Length	44'	Wheels	17 1/2" x 6 3/4" 8-bolt Disc
Deck Length	42' (8' Upper, 3' Taper, 26' Flat Deck, 5' Beavertail)	Tires	215/75R17.5" 16-PR Radial
Slope	3' Slope or Straight Drop	Jack Capacity	(2) 25,000 lb. 2-Speed
Overall Width	102"	Main Frame	12" Pierced I-Beam @ 35#
Deck Width	102"	Crossmembers	6" Channel 18" OC@ 8.2#
Deck Height	34"	Side Rail	8" Channel@ 11.5#
Beavertail	5' w/Wood	Decking	2" x 8" White Oak
Ramps	5' w/Spring Assist, w/Wood	Tie Downs	Rub Rail w/Stake Pockets
Hitch	Kingpin	Lights	Seal Beam Modular
Hitch Height	46"	Colors	Yellow or Black

Options

8WADL - Additional Deck Length (9' Max.)

HYR - Hydraulic Ramps

CBR - Cleated Beavertail and Ramps

TRS - Telescopic Ramps for straight drop neck

STM - Spare Tire Mount

CO - Color Options: Red, Blue or Green

SDN - Straight Drop on Neck