


## HLA25 - 25 Ton Capacity



### Standard Specifications

GVWR	61,690 lbs.	Axles	(3) 20K Airbrake Oil Bath Dexter
Empty Weight	11,690 lbs.	Suspension (Back)	Hutch 9700 (Back 2 Axles)
Maximum Payload	50,000 lbs. w/Adequate hitch load	Suspension (Front)	Cush Air Ride - Air Lift (Front Axle)
Overall Length	34'	Brakes	Air w/ABS & ASA 12 1/4" x 7 1/2"
Deck Length	28' (22' Flat w/6' Beavertail)	Wheels	17 1/2" x 6 3/4" 8-bolt Disc
Overall Width	102"	Tires	215/75R17.5" 16-PR Radial
Deck Width	102"	Jack Capacity	25,000 lb. 2-Speed
Deck Height	34"	Main Frame	12" Pierced I-Beam @ 35#
Beavertail	6' w/Wood	Crossmembers	6" Channel@ 8.2#
Ramps	6' w/Spring Assist, w/Wood	Side Rail	8" Channel@ 11.5#
Hitch	Adj. 3" Forged Eye	Decking	2" x 8" White Oak
Hitch Height	20" to 31"	Tie Downs	Rub Rail w/Stake Pockets
Tongue	Cold Form w/Lockable Toolbox	Lights	LED - Seal Beam Modular
		Colors	Yellow or Black

### Options

5THW - 5th Wheel w/King Pin	CBR - Cleated Beavertail and Ramps
8W5THW - 8" Wide 5th Wheel w/King Pin	FR - Feathered Ramps
8WADL - Additional Deck Length (3' Max.)	STM - Spare Tire Mount
DTSLG - Dual 2 Speed Landing Gear	CO - Color Options: Red, Blue or Green
HYR - Hydraulic Ramps	