

HTD18A - 20 Ton Capacity



Standard Specifications

GVWR	48,640 lbs.	Axles	(2) 20K Airbrake Oil Bath Dexter
Empty Weight	8,640 lbs.	Suspension	Hutch 9700
Maximum Payload	40,000 lbs. w/Adequate hitch load	Brakes	Air w/ABS & ASA 12 1/4" x 7 1/2"
Overall Length	31'	Wheels	17 1/2" x 6 3/4" 8-bolt Disc
Deck Length	25' (20' Flat w/5' Beavertail)	Tires	215/75R17.5" 16-PR Radial
Overall Width	96"	Jack Capacity	12,000 lb. w/Drop Foot
Deck Width	96"	Main Frame	12" Pierced I-Beam @ 30#
Deck Height	34"	Crossmembers	6" Channel@ 8.2#
Beavertail	5' w/Wood	Side Rail	8" Channel@ 11.5#
Ramps	5' Layover, w/Spring Assist, w/Wood	Decking	2" x 8" White Oak
Hitch	Adj. 3" Forged Eye	Tie Downs	Rub Rail w/Stake Pockets
Hitch Height	20" to 31"	Lights	Seal Beam Modular
Tongue	Cold Form w/Lockable Toolbox	Colors	Yellow or Black

Options

8W102 - 102" Wide	CBR - Cleated Beavertail and Ramps
5THW - 5th Wheel w/King Pin	SUR - Standup Ramps
8W5THW - 8" Wide 5th Wheel w/King Pin	8WARL - Additional Ramp Length (1' Max.)
8WADL - Additional Deck Length (4' Max.)	FR - Feathered Ramps
STSLG - Single 2 Speed Landing Gear	STM - Spare Tire Mount
DTSLG - Dual 2 Speed Landing Gear	LL - LED Lights
DSSLG - Dual Single Speed Landing Gear	CO - Color Options: Red, Blue or Green
3-20K - 3rd 20K Axle (makes it a 25 ton capacity)	