

HTHBH - 6 Ton Capacity



Standard Specifications

GVWR	16,900 lbs.	Axles	(2) 6K E-Z Lube Dexter w/Brakes
Empty Weight	4,900 lbs.	Suspension	Multi-Leaf Spring
Maximum Payload	12,000 lbs. w/Adequate hitch load	Brakes	Electric 12" x 2" w/break-a-way kit
Overall Length	27'	Wheels	16" x 6" Single 8-bolt
Deck Length	21' (16' Flat w/5' Beavertail)	Tires	LT235/85R16" 10-PR
Overall Width	96"	Jack Capacity	12,000 lb. w/Drop Foot
Deck Width	96"	Main Frame	10" Channel @ 15.3#
Deck Height	35"	Crossmembers	Double 3" Channel@ 7#
Beavertail	5' Cleated	Side Rail	6" Channel@ 8.2#
Ramps	5' Cleated Layover w/Spring Assist	Decking	2" x 8" Treated Pine
Hitch	Adj. 2 1/2" Eye	Tie Downs	Rub Rail w/Stake Pockets
Hitch Height	22" to 32"	Lights	DOT Sealed Rubber-Mounted w/Conduit
Tongue	Cold Form w/Tool Tray	Colors	Yellow or Black

Options

8WGN - Gooseneck w/Adjustable 2 5/16" Ball Hitch	FAR - Fully Adjustable Ramps
LTBL - Lockable Toolbox Lid	8WADL - Additional Deck Length (4' Max.)
8WOD - 2" x 8" White Oak Deck	8W102 - 102" Wide
SUR - Standup Ramps	MW - Modular Wiring
8WARL - Additional Ramp Length (1' Maximum)	STSLG - Single 2 Speed Landing Gear
FR - Feathered Ramps	TC - Trickle Charger for Break-A-Way
WIR&B - Wood Insert & Beavertail	STM - Spare Tire Mount
3"IH - 3" Eye Hitch	CO - Color Options: Red, Blue or Green
2 5/16"HDBH - 2 5/16" Heavy Duty Ball Hitch	PSP - Paver Special (See below for description)

Paver Special includes: 6' Beavertail w/wood - 6' fully adjustable standup ramps w/wood and feathered ends.