

## HTMBH - 6 Ton Capacity



### Standard Specifications

|                 |                                   |               |                                     |
|-----------------|-----------------------------------|---------------|-------------------------------------|
| GVWR            | 15,930 lbs.                       | Axles         | (2) 6K E-Z Lube Dexter w/Brakes     |
| Empty Weight    | 3,930 lbs.                        | Suspension    | Multi-Leaf Spring                   |
| Maximum Payload | 12,000 lbs. w/Adequate hitch load | Brakes        | Electric 12" x 2" w/break-a-way kit |
| Overall Length  | 27'                               | Wheels        | 16" x 6" Single 8-bolt              |
| Deck Length     | 21' (18' Flat w/3' Beavertail)    | Tires         | LT235/85R16" 10-PR                  |
| Overall Width   | 96"                               | Jack Capacity | 12,000 lb. w/Drop Foot              |
| Deck Width      | 96"                               | Main Frame    | 8" Channel @ 11.5#                  |
| Deck Height     | 31"                               | Crossmembers  | 4" Channel@ 4.5#                    |
| Beavertail      | 3' w/Wood                         | Side Rail     | 6" Channel@ 8.2#                    |
| Ramps           | 5' Cleated w/Spring Assist        | Decking       | 2" x 8" Treated Pine                |
| Hitch           | Adj. 2 1/2" Eye                   | Tie Downs     | Rub Rail w/Stake Pockets            |
| Hitch Height    | 17" to 21"                        | Lights        | DOT Sealed Rubber-Mounted w/Conduit |
| Tongue          | Cold Form w/Tool Tray             | Colors        | Yellow or Black                     |

### Options

|  |  |
|--|--|
| 8WGN - Gooseneck w/Adjustable 2 5/16" Ball Hitch | 8WADL - Additional Deck Length (4' Max.)         |
| LTBL - Lockable Toolbox Lid                      | 8W102 - 102" Wide                                |
| 8WOD - 2" x 8" White Oak Deck                    | TC - Trickle Charger for Break-A-Way             |
| MW - Modular Wiring                              | STM - Spare Tire Mount                           |
| 8WARL - Additional Ramp Length (1' Maximum)      | 8WSATG - 8' Wide Spring Assisted Tailgate        |
| WIR - Wood Insert Ramps                          | 8WSSATG - 8' Wide Split Spring Assisted Tailgate |
| 2 5/16"HDBH - 2 5/16" Heavy Duty Ball Hitch      | 3R - 3rd Ramp                                    |
| 3"IH - 3" Eye Hitch                              | LL - LED Lights                                  |
| CO - Color Options: Red, Blue or Green           |  |