

HTMBK - 4.4 Ton Capacity



Standard Specifications

GVWR	12,560 lbs.	Axles	(2) 4,400 lb. E-Z Lube Dexter w/Brakes
Empty Weight	3,760 lbs.	Suspension	Multi-Leaf Spring
Maximum Payload	8,800 lbs. w/Adequate hitch load	Brakes	Electric 10" x 2 1/4" w/break-a-way kit
Overall Length	27'	Wheels	15" x 6" White Spoke 6-bolt
Deck Length	21' (18' Flat w/3' Beavertail)	Tires	ST225/75R15" 8-PR
Overall Width	96"	Jack Capacity	12,000 lb. w/Drop Foot
Deck Width	96"	Main Frame	7" Channel @ 9.8#
Deck Height	30"	Crossmembers	3" Channel@ 3.5#
Beavertail	3' w/Wood	Side Rail	6" Channel@ 8.2#
Ramps	5' Cleated w/Spring Assist	Decking	2" x 8" Treated Pine
Hitch	Adj. 2 5/16" Ball Coupler	Tie Downs	Rub Rail w/Stake Pockets
Hitch Height	17" to 21"	Lights	DOT Sealed Rubber-Mounted w/Conduit
Tongue	Cold Form w/Tool Tray	Colors	Yellow or Black

Options

8WGN - Gooseneck w/Adjustable 2 5/16" Ball Hitch	8WADL - Additional Deck Length (4' Max.)
LTBL - Lockable Toolbox Lid	8W102 - 102" Wide
8WOD - 2" x 8" White Oak Deck	TC - Trickle Charger for Break-A-Way
MW - Modular Wiring	STM - Spare Tire Mount
2 1/2" IH - 2 1/2" Adjustable Eye Hitch	8WSATG - 8' Wide Spring Assisted Tailgate
8WARL - Additional Ramp Length (1' Maximum)	8WSSATG - 8' Wide Split Spring Assisted Tailgate
WIR - Wood Insert Ramps	3R - 3rd Ramp
LL - LED Lights	CO - Color Options: Red, Blue or Green
HSB - Hydraulic Surge Brakes	