

HBC10 16' Standard - 5 Ton Capacity



Standard Specifications

GVWR	12,960 lbs.	Axles	(2) 5,200 lb. E-Z Lube Dexter w/Brakes
Empty Weight	2,960 lbs.	Suspension	Multi-Leaf Spring
Maximum Payload	10,000 lbs. w/Adequate hitch load	Brakes	Electric 12" x 2" w/break-a-way kit
Overall Length	22'	Wheels	15" x 6" White Spoke 6-bolt
Deck Length	16'	Tires	ST225/75R15" 8-PR
Overall Width	102"	Jack Capacity	7,000 lb. w/Drop Foot
Deck Width	83"	Main Frame	6" x 4" x 3/8" Angle @ 12.3#
Deck Height	21"	Crossmembers	3" Channel@ 3.5#
Ramps	5' Cleated Adjustable	Decking	2" x 8" Treated Pine
Hitch	Adj. 2 5/16" Ball Coupler	Tie Downs	Rub Rail w/Stake Pockets
Hitch Height	16" to 24"	Lights	Seal Beam Modular w/Conduit
Fenders	Diamond Plate	Colors	Yellow or Black

Options

6WGN - Gooseneck w/Adjustable 2 5/16" Ball Hitch	WIR - Wood Insert Ramps
LTBL - Lockable Toolbox Lid	6WSATG - 6' Wide Spring Assisted Tailgate
6WOD - 2" x 8" White Oak Deck	6WSSATG - 6' Wide Split Spring Assisted Tailgate
2 1/2" IH - 2 1/2" Adjustable Eye Hitch	3R - 3rd Ramp
6WADL - Extra Deck Length (2' Maximum)	LL - LED Lights
STM - Spare Tire Mount	HSB - Hydraulic Surge Brakes
TC - Trickle Charger for Break-A-Way	CO - Color Options: Red, Blue or Green

On this model, the deck sits down in the frame giving it a lower deck height that makes it ideal for loading a Skid Steer.