

HBC10 - 3 1/2 Ton Capacity



Standard Specifications

GVWR	9,230 lbs.	Axles	(2) 3,500 lb. E-Z Lube Dexter w/Brakes
Empty Weight	2,230 lbs.	Suspension	Multi-Leaf Spring
Maximum Payload	7,000 lbs. w/Adequate hitch load	Brakes	Electric 10" x 2 1/4" w/break-a-way kit
Overall Length	20'	Wheels	14" x 5" White Spoke 5-bolt
Deck Length	14'	Tires	ST215/75R14" 6 PR
Overall Width	96"	Jack Capacity	2,000 lb Flip-Up
Deck Width	77"	Main Frame	3" x 5" x 5/16" Angle @ 8.2#
Deck Height	20"	Crossmembers	3" Channel @ 3.5#
Ramps	4' Cleated Fully Adjustable	Decking	2" X 8" Treated Pine
Hitch	Adj. 2 5/16" Ball Coupler	Tie Downs	4" Stake Pockets
Hitch Height	15" to 23"	Lights	DOT Sealed Rubber-Mounted w/Conduit
Fenders	Diamond Plate	Colors	Yellow or Black

Options

6WGN - Gooseneck w/Adjustable 2 5/16" Ball Hitch	WIR - Wood Insert Ramps
TBB - Toolbox Bottom in Tongue	6WSATG - 6' Wide Spring Assisted Tailgate
LTBL - Lockable Toolbox Lid	6WSSATG - 6' Wide Split Spring Assisted Tailgate
6WOD - 2" x 8" White Oak Deck	MW - Modular Wiring
2 1/2" IH - 2 1/2" Adjustable Eye Hitch	TC - Trickle Charger for Break-A-Way
6W102 - 102" Wide w/82" Deck Width	LL - LED Lights
6WADL - Extra Deck Length (2' Max)	3R - 3rd Ramp
JU2KTO7LK - 7,000 lb. Jack	HSB - Hydraulic Surge Brakes
STM - Spare Tire Mount	CO - Color Options: Red, Blue or Green

On this model, the deck sits down in the frame giving it a lower deck height that makes it ideal for loading a Skid Steer.