

HSL16 - 7 Ton Capacity



Standard Specifications

GVWR	16,640 lbs.	Axles	(2) 7K Oil Bath Dexter w/Brakes
Empty Weight	2,640 lbs.	Suspension	Multi-Leaf Spring
Maximum Payload	14,000 lbs. w/Adequate hitch load	Brakes	Electric 12" x 2" w/break-a-way kit
Overall Length	23'	Wheels	16" x 6" Single 8-bolt
Deck Length	17' (14' flat w/3' beavertail)	Tires	LT235/85R16" 14 PR
Overall Width	102"	Jack Capacity	7,000 lb w/Adjustable Foot
Deck Width	82"	Main Frame	7" Channel @ 9.8#
Deck Height	27"	Crossmembers	3" Channel @ 3.5#
Beavertail	3' w/wood	Decking	2" X 8" Treated Pine
Hitch	Adj. 2 1/2" Eye	Tie Downs	Rub Rail w/Stake Pockets
Hitch Height	24" to 32"	Lights	DOT Sealed Rubber-Mounted w/Conduit
Fenders	Diamond Plate	Colors	Yellow or Black

Options

6WGN - Gooseneck w/Adjustable 2 5/16" Ball Hitch	MW - Modular Wiring
LTBL - Lockable Toolbox Lid	3"IH - 3" Eye Hitch
JU7KTO12K - 12,000 lb. Heavy Duty Landing Gear	6WSATG - 6' Wide Spring Assisted Tailgate
6WOD - 2" x 8" White Oak Deck	6WSSATG - 6' Wide Split Spring Assisted Tailgate
6WARL - Additional Ramp Length	STM - Spare Tire Mount
WIR - Wood Insert Ramps	LL - LED Lights
6WADL - Additional Deck Length (4' Max)	3R - 3rd Ramp
2 5/16"HDBH - 2 5/16" Heavy Duty Ball Hitch	CO - Color Options: Red, Blue or Green
TC - Trickle Charger for Break-A-Way	

On this model, the deck is flush with the top of the frame which makes it ideal for loading pallets or other material from the side.