

HTDGE - 9 Ton Capacity



Standard Specifications

GVWR	24,730 lbs.	Axles	(2) 9K Oil Bath Dexter w/Brakes
Empty Weight	6,730 lbs.	Suspension	Multi-Leaf Spring
Maximum Payload	18,000 lbs. w/Adequate hitch load	Brakes	Electric / Self Adj. 12 1/4" x 3 3/8"
Overall Length	38'	Wheels	16" x 6" Dual 8-bolt
Deck Length	28' (23' Flat w/5' Beavertail)	Tires	LT235/85R16" 10-PR
Overall Width	96"	Jack Capacity	(2) 12,000 lb. w/Drop Foot
Deck Width	96"	Main Frame	10" Channel @ 15.3#
Deck Height	35"	Crossmembers	Double 3" Channel@ 7#
Beavertail	5' Cleated	Side Rail	6" Channel@ 8.2#
Ramps	5' Cleated w/Spring Assist	Decking	2" x 8" Treated Pine
Hitch	Adj. 2 5/16" Ball Coupler	Tie Downs	Rub Rail w/Stake Pockets
Hitch Height	42" Adjustable	Lights	DOT Sealed Rubber-Mounted w/Conduit
Tongue	Gooseneck w/Tool Tray	Colors	Yellow or Black

Options

LTBL - Lockable Toolbox Lid	FAR - Fully Adjustable Ramps
8WOD - 2" x 8" White Oak Deck	8WADL - Additional Deck Length (12' Max.)
8WARL - Additional Ramp Length (1' Max.)	8W102 - 102' Wide
FR - Feathered Ramps	MW - Modular Wiring
WIR&B - Wood Insert Ramps & Beavertail	DTSLG - Dual 2 Speed Landing Gear
TC - Trickle Charger for Break-A-Way	STM - Spare Tire Mount
PBT - Pop Up Beavertail	DON - 5' x 8' Deck on top of gooseneck
3R - 3rd Ramp	CO - Color Options: Red, Blue or Green
LL - LED Lights	WR - Wedge Shaped Ramp