

HTMGG - 7 Ton Capacity



Standard Specifications

GVWR	18,670 lbs.	Axles	(2) 7K Oil Bath Dexter w/Brakes
Empty Weight	4,670 lbs.	Suspension	Multi-Leaf Spring
Maximum Payload	14,000 lbs. w/Adequate hitch load	Brakes	Electric 12" x 2" w/break-a-way kit
Overall Length	33'	Wheels	16" x 6" Single 8-bolt
Deck Length	23' (20' Flat w/3' Beavertail)	Tires	LT235/85R16" 14-PR
Overall Width	96"	Jack Capacity	12,000 lb. w/Drop Foot
Deck Width	96"	Main Frame	8" Channel @ 11.5#
Deck Height	31"	Crossmembers	4" Channel@ 4.5#
Beavertail	3' w/Wood	Side Rail	6" Channel@ 8.2#
Ramps	5' Cleated w/Spring Assist	Decking	2" x 8" Treated Pine
Hitch	Adj. 2 5/16" Ball Coupler	Tie Downs	Rub Rail w/Stake Pockets
Hitch Height	42" Adjustable	Lights	DOT Sealed Rubber-Mounted w/Conduit
Tongue	Gooseneck w/Tool Tray	Colors	Yellow or Black

Options

LTBL - Lockable Toolbox Lid	8WADL - Additional Deck Length (5' Max.)
8WOD - 2" x 8" White Oak Deck	8W102 - 102" Wide
MW - Modular Wiring	TC - Trickle Charger for Break-A-Way
8WARL - Additional Ramp Length (1' Max.)	8WSATG - 8' Wide Spring Assisted Tailgate
WIR - Wood Insert Ramps	8WSSATG - 8' Wide Split Spring Assisted Tailgate
KP - Adj. King Pin	PBT - Pop Up Beavertail
STM - Spare Tire Mount	DON - 5' x 8' Deck on top of gooseneck
3R - 3rd Ramp	CO - Color Options: Red, Blue or Green
LL - LED Lights	