

HTLG 16 - 3 1/2 Ton Capacity



Standard Specifications

GVWR	9,170 lbs.	Axles	(2) 3,500 lb. Dexter w/Brakes
Empty Weight	2,170 lbs.	Suspension	Multi-Leaf Spring
Maximum Payload	7,000 lbs. w/Adequate hitch load	Brakes	Electric / 10" x 2 1/4"
Overall Length	21'	Wheels	14" x 5" White Spoke 5-bolt
Deck Length	16'	Tires	ST205/75R14" 6-PR
Overall Width	96"	Jack Capacity	5,000 lb. w/Foot
Deck Width	79"	Main Frame	3" x 4" x 1/4" Angle @ 5.8#
Deck Height	19 1/2"	Crossmembers	2" x 3" x 3/16" Angle @ 3.07#
Hitch	2 5/16" Ball Coupler	Decking	2" x 8" Treated Pine
Hitch Height	18"	Tie Downs	4" Stake Pockets
Loading Ramp	4' Spring Assist Tail Gate	Lights	DOT Sealed Rubber-Mounted
Cargo Rail	2" x 3" x 1/8" Angle 10 1/2" High	Colors	Yellow or Black

Options

ADJ25/16"BH - Adjustable 2 5/16" Ball Hitch	ASP - Additional Stake Pockets
ADJ21/2"IH - Adjustable 2 1/2" Eye Hitch	6W102 - 102" Wide w/84" Deck Width
TBB - Toolbox Bottom in Tongue	6WADL - Extra Deck Length (2' Maximum)
6WOD - 2" x 8" White Oak Deck	STG - Split Tailgate
MW - Modular Wiring	TC - Trickle Charger for Break-A-Way
4'FACR - 4' Fully Adjustable Cleated Ramps	HSB - Hydraulic Surge Brakes
LL - LED Lights	CO - Color Options: Red, Blue or Green