

HS14 - 7 Ton Capacity



Standard Specifications

GVWR	18,140 lbs.	Axles	(2) 7K Oil Bath Dexter w/Brakes
Empty Weight	4,140 lbs.	Suspension	Multi-Leaf Spring
Maximum Payload	14,000 lbs. w/Adequate hitch load	Brakes	Electric 12" x 2" w/break-a-way kit
Overall Length	22'	Wheels	16" x 6" Single 8-bolt
Deck Length	16' (14' Flat w/2' Beavertail)	Tires	LT235/85R16" 14-PR
Overall Width	96"	Jack Capacity	12,000 lb. w/Drop Foot
Deck Width	96"	Main Frame	10" Channel @ 15.3#
Deck Height	28"	Crossmembers	4" Channel@ 5.4#
Beavertail	2' w/Wood	Side Rail	6" Channel@ 8.2#
Ramps	5' Cleated w/Spring Assist	Decking	2" x 8" White Oak
Hitch	Adj. 2 1/2" Forged Eye	Tie Downs	(4) 1" D-Rings
Hitch Height	21" to 31"	Lights	DOT Sealed Rubber-Mounted w/Conduit
Tongue	Cold Form w/Tool Tray	Colors	Yellow or Black

Options

8WGN - Gooseneck w/Adj. 2 5/16" Ball Hitch	8WADL - Additional Deck Length (4' Max.)
LTBL - Lockable Toolbox Lid	8W102 - 102" Wide
ADR - Additional D-Rings	MW - Modular Wiring
8WARL - Additional Ramp Length (1' Max.)	TC - Trickle Charger for Break-A-Way
FR - Feathered Ramps	2 5/16"HDBH - 2 5/16" Heavy Duty Ball Hitch
WIR - Wood Insert Ramps	STM - Spare Tire Mount
FAR - Full Adjustable Ramps	STSLG - Single 2 Speed Landing Gear
3"IH - 3" Eye Hitch	CO - Color Options: Red, Blue or Green

Drive over style fenders allow this deckover model to have an extra low deck height of 28".