


HD 10 - 3,500 lb Capacity



Standard Specifications

GVWR	4,500 lbs.	Suspension	Multi-Leaf Spring
Empty Weight	1,000 lbs.	Brakes	Electric / 10" x 2 1/4" w/Break-A-Way kit
Maximum Payload	3,500 lbs. w/Adequate hitch load	Wheels	14" x 5" White Spoke 5-bolt
Overall Length	16'	Tires	ST215/75R14" 6-PR
Deck Length	10'	Jack Capacity	2,000 lb. Flip-up
Overall Width	96"	Main Frame	3" x 4" x 1/4" Angle @ 5.8#
Deck Width	72"	Crossmembers	2" x 2" x 1/4" Angle @ 3.19#
Deck Height	16"	Decking	1/8" Diamond Plate
Hitch	Adj. 2" Ball Coupler	Tie Downs	4" Stake Pockets
Hitch Height	14" to 22"	Lights	DOT Sealed Rubber-Mounted
Axles	(1) 3,500 lb. Dexter w/Brakes	Colors	Yellow or Black

Options

2 5/16" BH - Adjustable 2 5/16" Ball Hitch	6W102 - 102" Wide w/78" Deck Width
2 1/2" IH - 2 1/2" Adjustable Eye Hitch	6WADL - Extra Deck Length (2' Maximum)
6WOD - 2" x 8" White Oak Deck	MW - Modular Wiring
ASP - Additional Stake Pockets	TC - Trickle Charger for Break-A-Way
15" 6PT - ST225/75R15" 6 PR Tires	CO - Color Options: Red, Blue or Green