

HD 12 - 5,000 lb Capacity



Standard Specifications

GVWR	6,560 lbs.	Suspension	Multi-Leaf Spring
Empty Weight	1,560 lbs.	Brakes	Electric / 12" x 2" w/Break-A-Way kit
Maximum Payload	5,000 lbs. w/Adequate hitch load	Wheels	15" x 6" White Spoke 6-bolt
Overall Length	18'	Tires	ST225/75R15" 8-PR
Deck Length	12' 10"	Jack Capacity	2,000 lb. Flip-up
Overall Width	96"	Main Frame	6" x 4" x 3/8" Angle @ 12.3#
Deck Width	72"	Crossmembers	3" Channel@ 3.5#
Deck Height	17"	Decking	1/8" Diamond Plate
Hitch	Adj. 2 5/16" Ball Coupler	Tie Downs	4" Stake Pockets
Hitch Height	14" to 22"	Lights	DOT Sealed Rubber-Mounted
Axles	(1) 5,200 lb. Dexter w/Brakes	Colors	Yellow or Black

Options

2 1/2" IH - Adjustable Eye Hitch	6WADL - Extra Deck Length (2' Maximum)
6WOD - 2" x 8" White Oak Deck	MW - Modular Wiring
ASP - Additional Stake Pockets	TC - Trickle Charger for Break-A-Way
8BWSA - ST225/75R16 10 PR 8-bolt wheels	HSB - Hydraulic Surge Brakes
6W102 - 102" Wide w/78" Deck Width	CO - Color Options: Red, Blue or Green