

HD14 - 5 Ton Capacity



Standard Specifications

GVWR	12,590 lbs.	Axles	(2) 5,200 lb. E-Z Lube Dexter w/Brakes
Empty Weight	2,590 lbs.	Suspension	Multi-Leaf Spring
Maximum Payload	10,000 lbs. w/Adequate hitch load	Brakes	Electric / 12" x 2" w/Break-A-Way kit
Overall Length	22'	Wheels	15" x 6" White Spoke 6-bolt
Deck Length	16'	Tires	ST225/75R15" 8-PR
Approach Plate	18" Full Width	Jack Capacity	2,000 lb. Flip-up
Overall Width	96"	Main Frame	6" x 4" x 3/8" Angle @ 12.3#
Deck Width	72"	Crossmembers	3" Channel @ 3.5#
Deck Height	17"	Decking	1/8" Diamond Plate
Hitch	Adj. 2 1/2" Eye	Tie Downs	4" Stake Pockets
Hitch Height	10" to 18"	Lights	DOT Sealed Rubber-Mounted w/Conduit
Fenders	Diamond Plate	Colors	Yellow or Black

Options

6WGN - Gooseneck w/Adjustable 2 5/16" Ball Hitch	6WADL - Extra Deck Length (2' Max.)
LTBL - Lockable Toolbox Lid	MW - Modular Wiring
6WOD - 2" x 8" White Oak Deck	TC - Trickle Charger for Break-A-Way
6W102 - 102" Wide w/78" Deck Width	6WSD - 6' Wide Stationary Deck (4' Max.)
8BWTA - ST225/75R16 10 PR Tires w/ 8-bolt Wheels	LL - LED Lights
JU2KTO7K - 7,000 lbs. Jack	CO - Color Options: Red, Blue or Green
HSB - Hydraulic Surge Brakes	