

HSLT18 - 6 Ton Capacity



Standard Specifications

GVWR	15,230 lbs.	Axles	(2) 6K E-Z Lube Dexter w/Brakes
Empty Weight	3,230 lbs.	Suspension	Multi-Leaf Spring
Maximum Payload	12,000 lbs. w/Adequate hitch load	Brakes	Electric / 12" x 2" w/Break-A-Way kit
Overall Length	24'	Wheels	16" x 6" Single 8-bolt
Deck Length	18' (15' Flat w/3' taper)	Tires	LT235/85R16" 10-PR
Approach Plate	Full Width	Jack Capacity	7,000 lb. w/Adjustable Foot
Overall Width	102"	Main Frame	6" x 4" x 3/8" Angle @ 12.3#
Deck Width	82"	Crossmembers	3" Channel @ 3.5#
Deck Height	22"	Decking	2" x 8" Treated Pine
Hitch	Adj. 2 1/2" Eye	Tie Downs	Rub Rail w/Stake Pockets
Hitch Height	16" to 20"	Lights	DOT Sealed Rubber-Mounted w/Conduit
Fenders	Diamond Plate	Colors	Yellow or Black

Options

6WGN - Gooseneck w/Adjustable 2 5/16" Ball Hitch	6WADL - Extra Deck Length (2' Max.)
LTBL - Lockable Toolbox Lid	STM - Spare Tire Mount
6WOD - 2" x 8" White Oak Deck	TC - Trickle Charger for Break-A-Way
JU7KTO12K - 12,000 lb. Heavy Duty Landing Gear	2 5/16"HDBH - 2 5/16" Heavy Duty Ball Hitch
MW - Modular Wiring	LL - LED Lights
3"IH - 3" Eye Hitch	CO - Color Options: Red, Blue or Green
HSB - Hydraulic Surge Brakes	