

HTD20A - 20 Ton Capacity



Standard Specifications

GVWR	49,170 lbs.	Brakes	Air w/ABS & ASA 12 1/4" x 7 1/2"
Empty Weight	9,170 lbs.	Wheels	17 1/2" x 6 3/4" 8-Bolt Disc
Maximum Payload	40,000 lbs. w/Adequate hitch load	Tires	215/75R17 1/2" 16-PR Radial
Overall Length	31'	Jack Capacity	12,000 lb. w/Drop Foot
Deck Length	24' (16' Flat w/8' taper)	Under Frame	12" I-Beam @ 30#
Overall Width	96"	Upper Deck	Double 7" Channel @ 24.5#
Deck Width	96"	Crossmembers	6" Channel @ 8.2#
Deck Height	36"	Side Rails	8" Channel @ 11.5#
Hitch	Adj. 3" Forged Eye	Decking	2" x 8" White Oak
Hitch Height	14" to 25"	Tie Downs	Rub Rail w/Stake Pockets
Axles	(2) 20K Airbrake Oil Bath Dexter	Lights	Seal Beam Modular
Suspension	Hutch 9700	Colors	Yellow or Black

Options

8WSD - Stationary Deck (4' Max.)	8WADL - Additional Deck Length (4' Max.)
5THW - 5th Wheel w/King Pin	8W102 - 102" Wide
8W5THW - 8' Wide 5th Wheel w/King Pin	STSLG - Single 2 Speed Landing Gear
LTBL - Lockable Toolbox Lid	STR - Spare Tire & Rim
STM - Spare Tire Mount	CO - Color Options: Red, Blue or Green
SLL - LED Lights	