

HTTD20C - 12 Ton Capacity



Standard Specifications

GVWR	29,950 lbs.	Brakes	Electric / Self Adj. 12 1/4" x 5"
Empty Weight	5,950 lbs.	Wheels	16" x 6" Dual 8-bolt
Maximum Payload	24,000 lbs. w/Adequate hitch load	Tires	LT235/85R16" 10-PR
Overall Length	28'	Jack Capacity	12,000 lb. w/Drop Foot
Deck Length	22' (13' Flat w/9' taper)	Under Frame	6" I-Beam @ 25#
Overall Width	96"	Upper Deck	8" I-Beam @ 18#
Deck Width	96"	Crossmembers	Double 3" Channel @ 7#
Deck Height	35"	Side Rails	6" Channel @ 8.2#
Hitch	Adj. 3" Forged Eye	Decking	2" x 8" White Oak
Hitch Height	22" to 32"	Tie Downs	Rub Rail w/Stake Pockets
Axles	(2) 12K Oil Bath Dexter w/Brakes	Lights	DOT Sealed Rubber-Mounted w/Conduit
Suspension	Multi-Leaf Spring	Colors	Yellow or Black

Options

12KAB - Air Brakes w/ABS & ASA	8WSD - Stationary Deck (4' Max.)
5THW - 5th Wheel w/King Pin	8WADL - Additional Deck Length (4' Max.)
8W5THW - 8' Wide 5th Wheel w/King Pin	8W102 - 102" Wide
LTBL - Lockable Toolbox Lid	STSLG - Single 2 Speed Landing Gear
MW - Modular Wiring	LL - LED Lights
TC - Trickle Charger for Break-A-Way	CO - Color Options: Red, Blue or Green
STM - Spare Tire Mount	